

FILT'RAY 2-month in-line filter

Ref. AT030734

For rinsing medical devices



DESCRIPTION

FILT'RAY 2-month in-line filter

Ref. AT030734

AQUATOOLS anti-Legionella and all-germ in-line filter.
Suitable for filtering water to supply equipment used in the treatment of medical devices (e.g. endoscopes).
Device made from MBS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 6,000 litres.
Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the mixer/tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 2 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).
Sterile filter.
FILT'RAY 2G sterile disposable water filters are:
CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
Class I Medical Devices in Canada that comply with SOR/98-282.
Packaged in boxes of 10 pieces, each filter individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY 2-month in-line filter - Ref. AT030734

Technology	Point-of-use filtration
Flow rate	6.3 lpm at 3 bar and 2.2 lpm at 1 bar
Lifespan	2 months
Norms	ACS CE

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 2 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

