

Filtre robinet FILT'RAY Compact 3 mois

Ref. AT20351

Sterile



DESCRIPTION

Filtre robinet FILT'RAY Compact 3 mois

Ref. AT20351

AQUATOOLS anti-Legionella and all-germ tap filter, laminar spray.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 9,000 litres.
Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap/shower).
Space saving, suitable for taps with a low spout height: H. 50mm - Ø. 56mm.
Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 3 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total).
Sterile filter.
Medical device CE Class Is.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.

ADVANTAGES



Anti-legionella and all-germ



Space saving




Optimised position: angled connection



Lifespan: 3 months after installation

TECHNICAL CHARACTERISTICS

Filtre robinet FILT'RAY Compact 3 mois - Ref. AT20351

Technology	Point-of-use filtration
Height	50mm
Flow rate	4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	56mm
Lifespan	3 months
Norms	ACS  KTW 