

# FILT'RAY 2-month shower head filter

Ref. AT030713

Sterile



## DESCRIPTION

**FILT'RAY 2-month shower head filter**

**Ref. AT030713**

AQUATOOLS anti-Legionella and all-germ shower filter.  
Device made from MBS.  
Membrane type: tubular microfiltration.  
Membrane made from polyethylene.  
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
Filtration flow rate: 11.9 lpm at 3 bar and 4.5 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower).  
Maximum upstream pressure at the point-of-use: 5 bar.  
Maximum lifespan: 2 months from installation.  
Withstands thermal shocks: 70°C for 30 minutes.  
Withstands chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).  
Sterile filter.  
FILT'RAY 2G sterile disposable water filters are:  
CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;  
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;  
Class I Medical Devices in Canada that comply with SOR/98-282.  
Packaged in boxes of 10, each filter is individually wrapped and sterile.

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 2 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

## TECHNICAL CHARACTERISTICS

**FILT'RAY 2-month shower head filter - Ref. AT030713**

Connector	M1/2"
Technology	Point-of-use filtration
Height	70mm
Length	225mm
Flow rate	11.9 lpm at 3 bar, 4.5 lpm at 1 bar
Lifespan	2 months
Norms	ACS CE JWRAS

