

FILT'RAY tap filter, 4-months

Ref. AT030740

Non-sterile



DESCRIPTION

FILT'RAY tap filter, 4-months

Ref. AT030740

AQUATOOLS anti-Legionella and all-germ tap filter.
 Device made from MBS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 4 months from installation.
 Withstands thermal shocks: 70°C for 30 minutes.
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).
 Non-sterile filter.
 CE marked Class I medical device.
 Packaged in boxes of 10.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan 4 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY tap filter, 4-months - Ref. AT030740

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar and 2.2 lpm at 1 bar
Lifespan	4 months
Norms	ACS CE JWRAS

