

FILT'RAY 2G 3 month shower filter

Ref. AT030714

Sterile



DESCRIPTION

FILT'RAY 2G 3 month shower filter

Ref. AT030714

AQUATOOLS anti-Legionella and all-germ shower filter.
 Device made from MBS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Filtration flow rate: 11.9 lpm at 3 bar and 4.5 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower valve).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 3 months from installation.
 Withstands thermal shocks: 70°C for 30 minutes.
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total).
 Sterile filter.
 FILT'RAY 2G sterile disposable water filters are:
 CE marked Class Is Medical Devices in Europe that comply with directive 93/42/CEE;
 Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
 Class I Medical Devices in Canada that comply with SOR/98-282.
 Packaged in boxes of 10, each filter is individually wrapped and sterile.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 3 months from installation



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 3 month shower filter - Ref. AT030714

Supply	M1/2"
Technology	Point-of-use filtration
Height	70mm
Length	225mm
Flow rate	11.9 lpm at 3 bar and 4.5 lpm at 1 bar
Lifespan	3 months
Norms	ACS CE JWRAS

