

FILT'RAY Compact 2-month shower head filter

Ref. AT20261

Sterile



DESCRIPTION


FILT'RAY Compact 2-month shower head filter

Ref. AT20261

AQUATOOLS anti-Legionella and all-germ tap filter.
 Device made from ABS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Qualified water volume per duration of use: 6,000 litres.
 Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 2 months after installation.
 Resistance to thermal shocks: 70°C for 30 minutes.
 Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).
 Sterile filter.
 Medical device CE Class Is.
 Weight: empty filter 105g / full filter 186g.
 Reference for a single unit. Must be ordered in multiples of 10.
 Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 2-month shower head filter - Ref. AT20261

| | |
|-----------|---|
| Connector | M1/2" |
| Height | 62mm |
| Length | 194mm |
| Flow rate | 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar |
| Diameter | 56mm |
| Lifespan | 2 months |
| Norms | ACS    |

ADVANTAGES



Anti-legionella and all-germ



Space saving



Lifespan: 2 months after installation



Quick to install without tools

