

# FILT'RAY 4-month tap filter

Ref. AT030750

Sterile



## DESCRIPTION

**FILT'RAY 4-month tap filter**

**Ref. AT030750**

AQUATOOLS anti-Legionella and all-germ tap filter.

Device made from MBS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 4 months after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).

Sterile filter.

FILT'RAY sterile disposable water filters are:

CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;

Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;

Class I Medical Devices in Canada that comply with SOR/98-282.

Packaged in boxes of 10 units. Individually wrapped and sterile.

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 4 months from installation



Bubl'air Wash: extends filter life



Quick to install without tools

## TECHNICAL CHARACTERISTICS

**FILT'RAY 4-month tap filter - Ref. AT030750**

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	4 months
Norms	ACS CE W WWRAS

